

11-03-00

A

APPLICATION FOR U.S. PATENT
TRANSMITTAL FORM

Attorney Docket No. PHL Y-25,500

ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231JC9345 U.S. PTO
09/705514

11/02/00

Sir:

"EXPRESS MAIL" CERTIFICATE

Number: EL560083346USDate of Deposit: 11/2/00Transmitted herewith for filing is the patent application
of:Inventor(s): Jeffrey Jovan Philyaw and David
Kent MathewsI hereby certify that this paper or fee is being deposited with the United States Postal
Service -- "Express Mail Post Office to Addressee" Service under 37 C.F.R. 1.10 on the
date indicated above and is addressed to the Assistant Commissioner for Patents,
Washington, D.C. 20231

Signature of Person Mailing Application

11/2/00
Typed or Printed NameFor: METHOD FOR UTILIZING
VISUAL CUE IN
CONJUNCTION WITH WEB ACCESS

Enclosed are:

13 sheet(s) of informal drawings.

An unexecuted Declaration and Power of Attorney

An unexecuted Statement Claiming Small Entity Status -- Small Business Concern

FEE CALCULATION					FEE
	No.		No. Extra	Rate	Basic Fee \$355.00
Total Claims	32	- 20 =	12	X \$ 9	\$108.00
Independent Claims	2	- 3 =	0	X \$ 40	\$00.00
Total Filing Fee					\$463.00
Assignment Recording Fee					\$ 00.00
TOTAL FEES					\$463.00

Please direct all correspondence to: Gregory M. Howison, HOWISON, CHAUZA, HANDLEY &
ARNOTT, L.L.P., P.O. Box 741715, Dallas, Texas 75374-1715; Phone: 972/479-0462.11/2/00
DateAttorney for Applicant
Registration No. 30,646

RHCK/TRANSMIT.SML

**STATEMENT CLAIMING SMALL ENTITY STATUS --
SMALL BUSINESS CONCERN**

I hereby declare that I am an official of the small business concern identified below and am empowered to act on behalf of the concern:

Digital:Convergence Corporation
 9101 N. Central Expressway, Suite 600, Dallas, TX 75231

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 37 C.F.R. § 1.9 (d), for purposes of paying reduced fees, in that (1) the number of employees of the concern including those of its affiliates, does not exceed 500 persons, and (2) the concern has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey or license, any rights in the below-identified invention to any person who could not be classified as an independent inventor if the person had made the invention, or to any concern which would not qualify as a small business concern or as a nonprofit organization. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that exclusive rights to the invention have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled

A Combined Product Code and Insignia for Signifying an Internal Interactive Code

and for which application for Letters Patent of the United States is to be filed of even date herewith by inventor(s), Jeffry Jovan Philyaw and David Kent Mathews.

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small business entity is no longer appropriate. (37 C.F.R. § 1.29 (b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and may jeopardize the validity of the application or any patent issuing thereon.

Digital:Convergence Corporation

By: _____
 Jeffry Jovan Philyaw

Its: President _____

Date: _____

FILE NO. PHLY-25,509

**METHOD FOR UTILIZING VISUAL CUE IN CONJUNCTION WITH WEB
ACCESS**

Inventor(s):

Jeffry Jovan Philyaw and David Kent Mathews

Express Mail No. EL560083346US

Express Mail No. EL560083346US

FILE NO. PHL-25,509

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

**METHOD FOR UTILIZING VISUAL CUE IN CONJUNCTION WITH WEB
ACCESS**

TECHNICAL FIELD OF THE INVENTION

The present invention is related to a method of computer control and, more particularly, to a method for utilizing a visual cue in conjunction web access.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation-in-Part of pending U.S. Patent Application
5 Serial No. 09/382,421 (Atty. Dkt. No. PHL-24,740) entitled "A COMBINED
PRODUCT CODE AND INSIGNIA FOR SIGNIFYING AN INTERNAL
INTERACTIVE CODE," filed August 24, 1999, which is Continuation-in-Part of
pending U.S. Patent Application Serial No. 09/378,221 (Atty Dkt. No. PHL-24,669)
entitled "METHOD AND APPARATUS FOR ACCESSING A REMOTE LOCATION
10 BY SCANNING AN OPTICAL CODE," filed on August 19, 1999, which is a
Continuation-in-Part of the following two pending U.S. Patent Applications: Serial No.

09/151,471 (Atty Dkt. No. PHL Y-24,397) entitled "METHOD FOR INTERFACING
SCANNED PRODUCT INFORMATION WITH A SOURCE FOR THE PRODUCT
OVER A GLOBAL NETWORK," and Serial No. 09/151,530 (Atty Dkt. No. PHL Y-
24,398) entitled "METHOD FOR CONTROLLING A COMPUTER WITH AN
5 AUDIO SIGNAL," both filed on September 11, 1998; the present application being
related to the following pending U.S. Patent Applications: Serial No. _____ (Atty
Dkt. No. PHL Y-24,668) entitled "INTERACTIVE DOLL," filed on August 19, 1999;
Serial No. _____ (Atty Dkt. No. PHL Y-24,670) entitled "METHOD AND
APPARATUS FOR EMBEDDING ROUTING INFORMATION TO A REMOTE
10 WEB SITE IN AN AUDIO/VIDEO TRACK," filed on August 19, 1999; Serial No.
_____ (Atty Dkt. No. PHL Y-24,703) entitled "METHOD AND APPARATUS FOR
CONTROLLING A COMPUTER FROM A REMOTE LOCATION," filed on August
19, 1999; Serial No. _____ (Atty Dkt No. PHL Y-24,705) entitled "A METHOD
FOR CONTROLLING A COMPUTER USING AN EMBEDDED UNIQUE CODE IN
15 THE CONTENT OF VIDEO TAPE MEDIA," filed on August 19, 1999; Serial No.
_____ (Atty Dkt. No. PHL Y-24,706) entitled "A METHOD FOR
CONTROLLING A COMPUTER USING AN EMBEDDED UNIQUE CODE IN THE
CONTENT OF DVD MEDIA," filed on August 19, 1999; Serial No. _____ (Atty
Dkt. No. PHL Y-24,707) entitled "A METHOD FOR CONTROLLING A COMPUTER
20 USING AN EMBEDDED UNIQUE CODE IN THE CONTENT OF CD MEDIA,"
filed on August 19, 1999; Serial No. _____ (Atty Dkt. No. PHL Y-24,708) entitled
"A METHOD FOR CONTROLLING A COMPUTER USING AN EMBEDDED
UNIQUE CODE IN THE CONTENT OF DAT MEDIA," filed on August 19, 1999;
and related to the following co-pending U.S. Patent Applications filed on even date
25 with the present application: Serial No. _____ (Atty Dkt. No. PHL Y-24,731)
entitled "METHOD AND APPARATUS FOR OPENING AND LAUNCHING A
WEB BROWSER IN RESPONSE TO AN AUDIBLE SIGNAL;" Serial No.
_____ (Atty Dkt. No. PHL Y-24,732) entitled "METHOD AND APPARATUS
FOR COMPLETING, SECURING AND CONDUCTING AN E-COMMERCE

TRANSACTION;” Serial No. _____ (Atty Dkt. No. PHL Y-24,733) entitled
“METHOD AND APPARATUS FOR TRACKING USER PROFILE AND HABITS
ON A GLOBAL NETWORK;” Serial No. _____ (Atty Dkt. No. PHL Y-
24,734) entitled “METHOD AND APPARATUS FOR DIRECTING AN EXISTING
5 PRODUCT CODE TO A REMOTE LOCATION;” Serial No. _____ (Atty
Dkt. No. PHL Y-24,735) entitled “METHOD AND APPARATUS FOR LAUNCHING
A WEB SITE WITH A NON-STANDARD CONTROL INPUT DEVICE;” Serial No.
_____ (Atty Dkt. No. PHL Y-24,736) entitled “METHOD AND APPARATUS
FOR ALLOWING A BROADCAST TO REMOTELY CONTROL A COMPUTER;”
10 Serial No. _____ (Atty Dkt. No. PHL Y-24,737) entitled “METHOD AND
APPARATUS FOR LAUNCHING A WEB SITE IN RESPONSE TO SCANNING OF
A PRODUCT CODE;” Serial No. _____ (Atty Dkt. No. PHL Y-24,738)
entitled “METHOD AND APPARATUS FOR MATCHING A USER’S USE
PROFILE IN COMMERCE WITH A BROADCAST;” Serial No. _____
15 (Atty Dkt. No. PHL Y-24,739) entitled “METHOD AND APPARATUS FOR
UTILIZING AN AUDIBLE SIGNAL TO INDUCE A USER TO SELECT AN E-
COMMERCE FUNCTION;” Serial No. _____ (Atty Dkt. No. PHL Y-24,741)
entitled “DIGITAL ID FOR SELECTING WEB BROWSER AND USE
PREFERENCES OF A USER DURING USE OF A WEB APPLICATION;” Serial No.
20 _____ (Atty Dkt. No. PHL Y-24,742) entitled “UNIQUE ID FOR IDENTIFYING
A USER AND FACILITATING AN E-COMMERCE TRANSACTION;” Serial No.
_____ (Atty Dkt. No. PHL Y-24,743) entitled “METHOD AND APPARATUS
FOR LINKING A WEB BROWSER TO A PROMOTIONAL OFFER OVER A
GLOBAL NETWORK;” Serial No. _____ (Atty Dkt. No. PHL Y-24,744)
25 entitled “METHOD AND APPARATUS FOR CONTROLLING A USER’S PC
THROUGH AN AUDIO/VISUAL BROADCAST TO ARCHIVE INFORMATION IN
THE USER’S PC;” Serial No. _____ (Atty Dkt. No. PHL Y-24,745) entitled
“METHOD AND APPARATUS FOR UTILIZING AN EXISTING PRODUCT CODE
TO ISSUE A MATCH TO A PREDETERMINED LOCATION ON A GLOBAL

NETWORK;” Serial. No. _____ (Atty Dkt. No. PHL Y-24,747) entitled
“NETWORK ROUTING UTILIZING A PRODUCT CODE;” and Serial No.
_____ (Atty Dkt. No. PHL Y-24,748) entitled “METHOD FOR
INTERCONNECTING TWO LOCATIONS OVER A NETWORK IN RESPONSE TO
5 USING A TOOL.”

BACKGROUND OF THE INVENTION

With the growing numbers of computer users connecting to the "Internet," many companies are seeking the substantial commercial opportunities presented by such a large user base. For example, one technology which exists allows a television ("TV") signal to trigger a computer response in which the consumer will be guided to a personalized web page. The source of the triggering signal may be a TV, video tape recorder, or radio. For example, if a viewer is watching a TV program in which an advertiser offers viewer voting, the advertiser may transmit a unique signal within the television signal which controls a program known as a "browser" on the viewer's computer to automatically display the advertiser's web page. The viewer then simply makes a selection which is then transmitted back to the advertiser.

In order to provide the viewer with the capability of responding to a wide variety of companies using this technology, a database of company information and Uniform Resource Locator ("URL") codes is necessarily maintained in the viewer's computer, requiring continuous updates. URLs are short strings of data that identify resources on the Internet: documents, images, downloadable files, services, electronic mailboxes, and other resources. URLs make resources available under a variety of naming schemes and access methods such as HTTP, FTP, and Internet mail, addressable in the same simple way. URLs reduce the tedium of "login to this server, then issue this magic command ..." down to a single click. The Internet uses URLs to specify the location of files on other servers. A URL includes the type of resource being accessed (e.g., Web, gopher, FTP), the address of the server, and the location of the file. The URL can point to any file on any networked computer. Current technology requires the viewer to perform periodic updates to obtain the most current URL database. This aspect of the current technology is cumbersome since the update process requires downloading information to the viewer's computer. Moreover, the likelihood for error in performing the update, and the necessity of redoing the update in

the event of a later computer crash, further complicates the process. Additionally, current technologies are limited in the number of companies which may be stored in the database. This is a significant limitation since world-wide access presented by the Internet and the increasing number of companies connecting to perform on-line E-commerce necessitates a large database.

5

PHLY-25,509

SUMMARY OF THE INVENTION

The present invention disclosed and claimed herein comprises a visual indicia or cue for facilitating computer based access of a network by a consumer witnessing a presentation. A visual indicia or cue is provided during the presentation indicative of a relationship between the visual indicia or cue and the presence of a location on a network. This allows this location on the network to be accessed by a computer having an appropriate input device for responding to a launch signal associated with the visual indicia or cue wherein such response of the input device will connect the computer to the location.

5

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying Drawings in which:

- 5 FIGURE 1 illustrates a block diagram of the preferred embodiment;
 FIGURE 2 illustrates the computer components employed in this embodiment;
 FIGURE 3 illustrates system interactions over a global network;
 FIGURES 4a-4e illustrate the various message packets transmitted between the
source PC and network servers used in the preferred embodiment; and
- 10 FIGURE 5 is a flowchart depicting operation of the system according to the
preferred embodiment.
- FIGURE 6 illustrates a flowchart of actions taken by the Advertiser Reference
Server (“ARS”) server;
- FIGURE 7 illustrates a flowchart of the interactive process between the source
15 computer and ARS;
- FIGURE 8 illustrates a web browser page receiving the modified
URL/advertiser product data according to the preferred embodiment;
- FIGURE 9 illustrates a simplified block diagram of the disclosed embodiment;
 FIGURE 10 illustrates a more detailed, simplified block diagram of the
20 embodiment of FIGURE 9;
- FIGURE 11 illustrates a diagrammatic view of a method for performing the
routing operation;
- FIGURE 12 illustrates a block diagram of an alternate embodiment utilizing an
optical region in the video image for generating the routing information;
- 25 FIGURE 13 illustrates a block diagram illustrating the generation of a profile
with the disclosed embodiment;
- FIGURE 14 illustrates a flowchart for generating the profile and storing at the
ARS;

FIGURE 15 illustrates a flowchart for processing the profile information when information is routed to a user;

FIGURE 16 illustrates a general block diagram of a disclosed embodiment;

FIGURE 16a illustrates a flowchart depicting the operation wherein the input device is registered;

FIGURE 17 illustrates the conversion circuit of the wedge interface;

FIGURE 18 illustrates a sample message packet transmitted from the user PC to the ARS;

FIGURE 19 illustrates a more detailed block diagram of the routing of the message packets between the various nodes;

FIGURE 20 illustrates a block diagram of a browser window, according to a disclosed embodiment;

FIGURE 21 illustrates a diagrammatic view of information contained in the ARS database;

FIGURE 22 illustrates a flowchart of the process of receiving information for the user's perspective;

FIGURE 23 illustrates a flowchart according to the ARS; and

FIGURE 24 illustrates a flowchart of the process performed at the E-commerce node; and

FIGURES 25a and 25b illustrate the operation wherein a bar code is associated with a unique indicia.

FIGURE 26 illustrates a block diagram of an alternate embodiment;

FIGURE 26a illustrates a diagrammatic view of the interaction between a user viewing a broadcast and a computer display;

FIGURE 27 illustrates one embodiment of a visual cue;

FIGURE 28a illustrates a first cell of an animation sequence involving a visual cue;

FIGURE 28b illustrates a second cell of an animation sequence involving a visual cue;

FIGURE 28c illustrates a third cell of an animation sequence involving a visual cue;

FIGURE 29a illustrates a first cell of an alternate animation sequence involving a visual cue;

5 FIGURE 29b illustrates a second cell of the alternate animation sequence of FIGURE 29a;

FIGURE 29c illustrates a third cell of the alternate animation sequence of FIGURE 29a;

10 FIGURE 30 illustrates a flowchart of one embodiment of the operation of the embodiment of FIGURE 26.

PHLY-25,509

DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIGURE 1, there is illustrated a block diagram of a system for controlling a personal computer ("PC") 112 via an audio tone transmitted over a wireless system utilizing a TV. In the embodiment illustrated in FIGURE 1, there is provided a transmission station 101 and a receive station 117 that are connected via a communication link 108. The transmission station 101 is comprised of a television program source 104, which is operable to generate a program in the form of a broadcast signal comprised of video and audio. This is transmitted via conventional techniques along channels in the appropriate frequencies. The program source is input to a mixing device 106, which mixing device is operable to mix in an audio signal. This audio signal is derived from an audio source 100 which comprises a coded audio signal which is then modulated onto a carrier which is combined with the television program source 104. This signal combining can be done at the audio level, or it can even be done at the RF level in the form of a different carrier. However, the preferred method is to merely sum the audio signal from the modulator 102 into the audio channel of the program that is generated by the television program source 104. The output thereof is provided from the mixing device 106 in the form of broadcast signal to an antenna 107, which transmits the information over the communication link 108 to an antenna 109 on the receive side.

On the receive side of the system, a conventional receiver 110, such as a television is provided. This television provides a speaker output which provides the user with an audible signal. This is typically associated with the program. However, the receiver 110 in the disclosed embodiment, also provides an audio output jack, this being the type RCA jack. This jack is utilized to provide an audio output signal on a line 113 which is represented by an audio signal 111. This line 113 provides all of the audio that is received over the communication link 108 to the PC 112 in the audio input port on the PC 112. However, it should be understood that, although a direct

connection is illustrated from the receiver 110 to the PC 112, there actually could be a microphone pickup at the PC 112 which could pick the audio signal up. In the disclosed embodiment the audio signal generated by the advertiser data input device 100 is audible to the human ear and, therefore, can be heard by the user. Therefore, no special filters are needed to provide this audio to the PC 112.

The PC 112 is operable to run programs thereon which typically are stored in a program file area 116. These programs can be any type of programs such as word processing programs, application programs, etc. In the disclosed embodiment, the program that is utilized in the system is what is referred to as a "browser." The PC 112 runs a browser program to facilitate the access of information on the network, for example, a global communication network known as the "Internet" or the World-Wide-Web ("Web"). The browser is a hypertext-linked application used for accessing information. Hypertext is a term used to describe a particular organization of information within a data processing system, and its presentation to a user. It exploits the computer's ability to link together information from a wide variety of sources to provide the user with the ability to explore a particular topic. The traditional style of presentation used in books employs an organization of the information which is imposed upon it by limitations of the medium, namely fixed sized, sequential paper pages. Hypertext systems, however, use a large number of units of text or other types of data such as image information, graphical information, video information, or sound information, which can vary in size. A collection of such units of information is termed a hypertext document, or where the hypertext documents employ information other than text, hypermedia documents. Multimedia communications may use the Hypertext Transfer Protocol ("HTTP"), and files or formatted data may use the Hypertext Markup Language ("HTML"). This formatting language provides for a mingling of text, graphics, sound, video, and hypertext links by "tagging" a text document using HTML. Data encoded using HTML is often referred to as an "HTML document," an "HTML page," or a "home page." These documents and other Internet resources may be

accessed across the network by means of a network addressing scheme which uses a locator referred to as a Uniform Resource Locator ("URL"), for example, "http://www.digital.com."

5 The Internet is one of the most utilized networks for interconnecting distributed computer systems and allows users of these computer systems to exchange data all over the world. Connected to the Internet are many private networks, for example, corporate or commercial networks. Standard protocols, such as the Transport Control Protocol ("TCP") and the Internet Protocol ("IP") provide a convenient method for communicating across these diverse networks. These protocols dictate how data are
10 formatted and communicated. As a characteristic of the Internet, the protocols are layered in an IP stack. At higher levels of the IP stack, such as the application layer (where HTTP is employed), the user information is more readily visible, while at lower levels, such as the network level (where TCP/IP are used), the data can merely be observed as packets or a stream of rapidly moving digital signals. Superimposed on the
15 Internet is a standard protocol interface for accessing Web resources, such servers, files, Web pages, mail messages, and the like. One way that Web resources can be accessed is by browsers made by *Netscape®* and *Microsoft Internet Explorer®*.

Referring again now to FIGURE 1, the user can load this program with the appropriate keystrokes such that a browser window will be displayed on a display 118.
20 In one embodiment, the user can run the browser program on the PC 112 such that the browser window is displayed on the display 118. While watching a preferred program, the user can also view display 118. When an audio signal is received by the receiver 110 and the encoded information is contained therein that was input thereto by the advertiser, the PC 112 will then perform a number of operations. The first operation,
25 according to the disclosed embodiment, is to extract the audio information within the received audio signal in the form of digital data, and then transmit this digital data to a defined location on the global communication network via a modem connection 114.

This connection will be described hereinbelow. This information will be relayed to a proprietary location and the instructions sent back to the PC 112 as to the location of the advertiser associated with the code, and the PC 112 will then effect a communication link to that location such that the user can view on the display 118 information that the advertiser, by the fact of putting the tone onto the broadcast channel, desires the viewer to view. This information can be in the form of interactive programs, data files, etc. In one example, when an advertisement appears on the television, the tone can be generated and then additional data displayed on the display 118. Additionally, a streaming video program could be played on the PC received over the network, which streaming video program is actually longer than the advertising segment on the broadcast. Another example would be a sports game that would broadcast the tone in order to allow a user access to information that is not available over the broadcast network, such as additional statistics associated with the sports program, etc.

By utilizing the system described herein with respect to the disclosed embodiment of FIGURE 1, an advertiser is allowed the ability to control a user's PC 112 through the use of tones embedded within a program audio signal. As will be described hereinbelow, the disclosed embodiment utilizes particular routing information stored in the PC 112 which allows the encoded information in the received audio signal to route this information to a desired location on the network and then allow other routing information to be returned to the PC 112 for control thereof to route the PC 112 to the appropriate location associated with that code.

Referring now to FIGURE 2, there is illustrated a computer 204, similar to computer 112, connected to display information on display 118. The computer 204 comprises an internal audio or "sound" card 206 for receiving the transmitted audio signal through receive antenna 109 and receiver 110. The sound card 206 typically contains analog-to-digital circuitry for converting the analog audio signal into a digital

signal. The digital signal may then be more easily manipulated by software programs. The receiver 110 separates the audio signal from the video signal. A special trigger signal located within the transmitted advertiser audio signal triggers proprietary software running on the computer 204 which launches a communication application, in this particular embodiment, the web browser application located on the PC 204. Coded advertiser information contained within the audio signal is then extracted and appended with the address of a proprietary server located on the communication network. The remote server address is in the form of a URL. This appended data, in addition to other control codes, is inserted directly into the web browser application for automatic routing to the communication network.

The web browser running on PC 204, and communicating to the network with a through an internal modem 208, in this embodiment, transmits the advertiser information to the remote server. The remote server cross-references the advertiser product information to the address of the advertiser server located on the network. The address of the advertiser server is routed back through the PC 204 web browser to the advertiser server. The advertiser product information is returned to PC 204 to be presented to the viewer on display 118. In this particular embodiment, the particular advertiser product information displayed is contained within the advertiser's web page 212. As mentioned above, the audio signal is audible to the human ear. Therefore the audio signal, as emitted from the TV speakers, may be input to the sound card 206 via a microphone. Furthermore, the audio signal need not be a real-time broadcast, but may be on video tapes, CDs, DVD, or other media which may be displayed at a later date. With the imminent implementation of high definition digital television, the audio signal output from the TV may also be digital. Therefore, direct input into a sound card for A/D purposes may not be necessary, but alternative interfacing techniques to accommodate digital-to-digital signal formats would apply.

Referring now to FIGURE 3, there is illustrated a source PC 302, similar to PCs 204 and 112, connected to a global communication network 306 through an interface 304. In this embodiment, the audio signal 111 is received by PC 302 through its sound card 206. The audio signal 111 comprises a trigger signal which triggers proprietary software into launching a web browser application residing on the PC 302. The audio signal 111 also comprises advertiser product information which is extracted and appended with URL information of an Advertiser Reference Server (“ARS”) 308. The ARS 308 is a system disposed on the network that is defined as the location to which data in the audio signal 111 is to be routed. As such, data in the audio signal 111 will always be routed to the ARS 308, since a URL is unique on the network system. Connected to the ARS 308 is a database 310 of product codes and associated manufacturer URLs. The database 310 undergoes a continual update process which is transparent to the user. As companies sign-on, e.g., subscribe, to this technology, manufacturer and product information is added to the database 310 without interrupting operation of the source PC 302 with frequent updates. When the advertiser server address URL is obtained from the ARS database 310, it and the request for the particular advertiser product information is automatically routed back through the web browser on PC 302, over to the respective advertiser server for retrieval of the advertiser product information to the PC 302. It should be noted that although the disclosed invention discusses a global communication network, the system is also applicable to LANs, WANs, and peer-to-peer network configurations. It should be noted that the disclosed architecture is not limited to a single source PC 302, but may comprise a plurality of source PCs, e.g., PC 300 and PC 303. Moreover, a plurality of ARS 308 systems and advertiser servers 312 may be implemented, e.g., ARS 314, and advertiser server A 316, respectively.

The information transactions, in general, which occur between the networked systems of this embodiment, over the communication network, are the following. The web browser running on source PC 302 transmits a message packet to the ARS 308

over Path "A." The ARS 308 decodes the message packet and performs a cross-reference function with product information extracted from the received message packet to obtain the address of an advertiser server 312. A new message packet is assembled comprising the advertiser server 312 address, and sent back to the source PC 302 over Path "B." A "handoff" operation is performed whereby the source PC 302 browser simply reroutes the information on to the advertiser server 312 over Path "C," with the appropriate source and destination address appended. The advertiser server 312 receives and decodes the message packet. The request-for-advertiser-product-information is extracted and the advertiser 312 retrieves the requested information from its database for transmission back to the source PC 302 over Path "D." The source PC 302 then processes the information, i.e., for display to the viewer. The optional Path "E" is discussed hereinbelow. It should be noted that the disclosed methods are not limited to only browser communication applications, but may accommodate, with sufficient modifications by one skilled in the art, other communication applications used to transmit information over the Internet or communication network.

Referring now to FIGURE 4a, the message packet 400 sent from the source PC 302 to ARS 308 via Path "A" comprises several fields. One field comprises the URL of the ARS 308 which indicates where the message packet is to be sent. Another field comprises the advertiser product code or other information derived from the audio signal 111, and any additional overhead information required for a given transaction. The product code provides a link to the address of the advertiser server 312, located in the database 310. Yet another field comprises the network address of the source PC 302. In general, network transmissions are effected in packets of information, each packet providing a destination address, a source address, and data. These packets vary depending upon the network transmission protocol utilized for communication. Although the protocols utilized in the disclosed embodiment are of a conventional protocol suite commonly known as TCP/IP, it should be understood that any protocols providing the similar basic functions can be used, with the primary requirement that a

browser can forward the routing information to the desired URL in response to keystrokes being input to a PC. However, it should be understood that any protocol can be used, with the primary requirement that a browser can forward the product information to the desired URL in response to keystrokes being input to a PC. Within the context of this disclosure, “message packet” shall refer to and comprise the destination URL, product information, and source address, even though more than a single packet must be transmitted to effect such a transmission.

Upon receipt of the message packet 400 from source PC 302, ARS 308 processes the information in accordance with instructions embedded in the overhead information. The ARS 308 specifically will extract the product code information from the received packet 400 and, once extracted, will then decode this product code information. Once decoded, this information is then compared with data contained within the ARS advertiser database 310 to determine if there is a “hit.” If there is no “hit” indicating a match, then information is returned to the browser indicating such. If there is a “hit,” a packet 402 is assembled which comprises the address of the source PC 302, and information instructing the source PC 302 as to how to access, directly in a “handoff” operation, another location on the network, that of an advertiser server 312. This type of construction is relatively conventional with browsers such as *Netscape®* and *Microsoft Internet Explorer®* and, rather than displaying information from the ARS 308, the source PC 302 can then access the advertiser server 312. The ARS 308 transmits the packet 402 back to source PC 302 over Path “B.” Referring now to FIGURE 4b, the message packet 402 comprises the address of the source PC 302, the URL of the advertiser server 312 embedded within instructional code, and the URL of the ARS 308.

Upon receipt of the message packet 402 by the source PC 302, the message packet 402 is disassembled to obtain pertinent routing information for assembly of a new message packet 404. The web browser running on source PC 302 is now directed

to obtain, over Path “C,” the product information relevant to the particular advertiser server 312 location information embedded in message packet 404. Referring now to FIGURE 4c, the message packet 404 for this transaction comprises the URL of the advertiser server 312, the request-for-product-information data, and the address of the source PC 302.

Upon receipt of the message packet 404 from source PC 302, advertiser server 312 disassembles the message packet 404 to obtain the request-for-product-information data. The advertiser server 312 then retrieves the particular product information from its database, and transmits it over Path “D” back to the source PC 302. Referring now to FIGURE 4d, the message packet 406 for this particular transaction comprises the address of the source PC 302, the requested information, and the URL of the advertiser server 312.

Optionally, the ARS 308 may make a direct request for product information over Path “E” to advertiser server 312. In this mode, the ARS 308 sends information to the advertiser server 312 instructing it to contact the source PC 302. This, however, is unconventional and requires more complex software control. The message packet 408 for this transaction is illustrated in FIGURE 4e, which comprises the URL of the advertiser server 312, the request-for-product-information data, and the address of the source PC 302. Since product information is not being returned to the ARS 308, but directly to the source PC 302, the message packet 408 requires the return address to be that of the source PC 302. The product information is then passed directly to PC 302 over Path “D.”

Referring now to FIGURE 5, the method for detecting and obtaining product information is as follows. In decision block 500, a proprietary application running resident on a source computer PC 302 (similar to PC 204) monitors the audio input for a special trigger signal. Upon detection of the trigger signal, data following the trigger

signal is decoded for further processing, in function block 502. In function block 504, the data is buffered for further manipulation. In decision block 506, a determination is made as to whether the data can be properly authenticated. If not, program flow continues through the “N” signal to function block 520 where the data is discarded. In function block 522, the program then signals for a retransmission of the data. The system then waits for the next trigger signal, in decision block 500. If properly authenticated in decision block 506, program flow continues through the “Y” signal path where the data is then used to launch the web browser application, as indicated in function block 508. In function block 510, the web browser receives the URL data, which is then automatically routed through the computer modem 208 to the network interface 304 and ultimately to the network 306. In function block 514, the ARS 308 responds by returning the URL of advertiser server 312 to the PC 302. In function block 516, the web browser running on the source PC 302, receives the advertiser URL information from the ARS 308, and transmits the URL for the product file to the advertiser server 312. In block 518, the advertiser server 312 responds by sending the product information to the source PC 302 for processing.

The user may obtain the benefits of this architecture by simply downloading the proprietary software over the network. Other methods for obtaining the software are well-known; for example, by CD, diskette, or pre-loaded hard drives.

Referring now to FIGURE 6, there is illustrated a flowchart of the process the ARS 308 may undergo when receiving the message packet 400 from the source PC 302. In decision block 600, the ARS 308 checks for the receipt of the message packet 400. If a message packet 400 is not received, program flow moves along the “N” path to continue waiting for the message. If the message packet 400 is received, program flow continues along path “Y” for message processing. Upon receipt of the message packet 400, in function block 602, the ARS 308 decodes the message packet 400. The product code is then extracted independently in function block 604 in preparation for matching

the product code with the appropriate advertiser server address located in the database 310. In function block 606, the product code is then used with a lookup table to retrieve the advertiser server 312 URL of the respective product information contained in the audio signal data. In function block 608, the ARS 308 then assembles message packet 402 for transmission back to the source PC 302. Function block 610 indicates the process of sending the message packet 402 back to the source PC 302 over Path "B."

Referring now to FIGURE 7, there is illustrated a flowchart of the interactive processes between the source PC 302 and the advertiser server 312. In function block 700, the source PC 302 receives the message packet 402 back from the ARS 308 and begins to decode the packet 402. In function block 702, the URL of the advertiser product information is extracted from the message packet 402 and saved for insertion into the message packet 404 to the advertiser server 312. The message packet 404 is then assembled and sent by the source PC 302 over Path "C" to the advertiser server 312, in function block 704. While the source PC 302 waits, in function block 706, the advertiser server 312 receives the message packet 404 from the source PC 302, in function block 708, and disassembles it. The product information location is then extracted from the message packet 404 in function block 710. The particular product information is retrieved from the advertiser server 312 database for transmission back to the source PC 302. In function block 712, the product information is assembled into message packet 406 and then transmitted back to the source PC 302 over Path "D." Returning to the source PC 302 in function block 714, the advertiser product information contained in the message packet 406 received from the advertiser server 312, is then extracted and processed in function block 716.

Referring now to FIGURE 8, after receipt of a trigger signal, a web browser application on a source PC 302 is automatically launched and computer display 800 presents a browser page 802. Proprietary software running on the source PC 302 processes the audio signal data after being digitized through the sound card 206. The

software appropriately prepares the data for insertion directly into the web browser by extracting the product information code and appending keystroke data to this information. First, a URL page 804 is opened in response to a Ctrl-O command added by the proprietary software as the first character string. Opening URL page 804 automatically positions the cursor in a field 806 where additional keystroke data following the Ctrl-O command will be inserted. After URL page 804 is opened, the hypertext protocol preamble http:// is inserted into the field 806. Next, URL information associated with the location of the ARS 308 is inserted into field 806. Following the ARS 308 URL data are the characters /? to allow entry of variables immediately following the /? characters. In this embodiment, the variable following is the product information code received in the audio signal. The product code information also provides the cross-reference information for obtaining the advertiser URL from the ARS database 310. Next, a carriage return is added to send the URL/product data and close the window 804. After the message packet 400 is transmitted to the ARS 308 from the source PC 302, transactions from the ARS308, to the source PC 302, to the advertiser server 312, and back to the source PC 302, occur quickly and are transparent to the viewer. At this point, the next information the viewer sees is the product information which was received from the advertiser server 312.

Referring now to FIGURE 9, there is illustrated a block diagram of a more simplified embodiment. In this embodiment, a video source 902 is provided which is operable to provide an audio output on an audio cable 901 which provides routing information referred to by reference numeral 904. The routing information 904 is basically information contained within the audio signal. This is an encoded or embedded signal. The important aspect of the routing information 904 is that it is automatically output in realtime as a function of the broadcast of the video program received over the video source 902. Therefore, whenever the program is being broadcast in realtime to the user 908, the routing information 904 will be output whenever the producer of the video desires it to be produced. It should be understood

that the box 902 representing the video source could be any type of media that will result in the routing information being output. This could be a cassette player, a DVD player, an audio cassette, a CD ROM or any such media. It is only important that this is a program that the producer develops which the user 908 watches in a continuous or a streaming manner. Embedded within that program, at a desired point selected by the producer, the routing information 904 is output.

The audio information is then routed to a PC 906, which is similar to the PC 112 in FIGURE 1. A user 908 is interfaced with the PC to receive information thereof, the PC 906 having associated therewith a display (not shown). The PC 906 is interfaced with a network 910, similar to the network 306 in FIGURE 3. This network 910 has multiple nodes thereon, one of which is the PC 906, and another of which is represented by a network node 912 which represents remote information. The object of the present embodiment is to access remote information for display to the user 908 by the act of transmitting from the video program in block 902 the routing information 904. This routing information 904 is utilized to allow the PC 906 which has a network "browser" running thereon to "fetch" the remote information at the node 912 over the network 910 for display to the user 908. This routing information 904 is in the form of an embedded code within the audio signal, as was described hereinabove.

Referring now to FIGURE 10, there is illustrated a more detailed block diagram of the embodiment of FIGURE 9. In this embodiment, the PC 906 is split up into a couple of nodes, a first PC 1002 and a second PC 1004. The PC 1002 resides at the node associated with the user 908, and the PC 1004 resides at another node. The PC 1004 represents the ARS 308 of FIGURE 3. The PC 1004 has a database 1006 associated therewith, which is basically the advertiser database 310. Therefore, there are three nodes on the network 910 necessary to implement the disclosed embodiment, the PC 1002, the PC 1004 and the remote information node 912. The routing information 904 is utilized by the PC 1002 for routing to the PC 1004 to determine the

location of the remote information node 912 on the network 910. This is returned to the PC 1002 and a connection made directly with the remote information node 912 and the information retrieved therefrom to the user 908. The routing information 904 basically constitutes primary routing information.

5 Referring now to FIGURE 11, there is illustrated a diagrammatic view of how the network packet is formed for sending the primary routing information to the PC 1004. In general, the primary routing information occupies a single field which primary routing information is then assembled into a data packet with the secondary routing information for transfer to the network 910. This is described hereinabove in detail.

10 Referring now to FIGURE 12, there is illustrated an alternate embodiment to that of FIGURE 9. In this embodiment, the video source 902 has associated therewith an optical region 1202, which optical region 1202 has disposed therein an embedded video code. This embedded video code could be relatively complex or as simple as a grid of dark and white regions, each region in the grid able to have a dark color for a logic "1" or a white region for a logic "0." This will allow a digital value to be
15 disposed within the optical region 1202. A sensor 1204 can then be provided for sensing this video code. In the example above, this would merely require an array of optical detectors, one for each region in the grid to determine whether this is a logic "1" or a logic "0" state. One of the sensed video is then output to the PC 906 for processing
20 thereof to determine the information contained therein, which information contained therein constitutes the primary routing information 904. Thereafter, it is processed as described hereinabove with reference to FIGURE 9.

25 Referring now to FIGURE 13, there is illustrated a block diagram for an embodiment wherein a user's profile can be forwarded to the original subscriber or manufacturer. The PC 906 has associated therewith a profile database 1302, which

profile database 1302 is operable to store a profile of the user 908. This profile is created when the program, after initial installation, requests profile information to be input in order to activate the program. In addition to the profile, there is also a unique ID that is provided to the user 908 in association with the browser program that runs on the PC 906. This is stored in a storage location represented by a block 1304. This ID 1304 is accessible by a remote location as a "cookie" which is information that is stored in the PC 906 in an accessible location, which accessible location is actually accessible by the remote program running on a remote node.

The ARS 308, which basically constitutes the PC 1004 of FIGURE 10, is operable to have associated therewith a profile database 1308, which profile database 1308 is operable to store profiles for all of the users. The profile database 1308 is a combination of the stored in profile database 1302 for all of the PCs 906 that are attachable to the system. This is to be distinguished from information stored in the database 310, the advertiser's database, which contains intermediate destination tables. When the routing information in the primary routing information 904 is forwarded to the ARS 308 and extracted from the original data packet, the lookup procedure described hereinabove can then be performed to determine where this information is to be routed. The profile database 1302 is then utilized for each transaction, wherein each transaction in the form of the routing information received from the primary routing information 904 is compared to the destination tables 310 to determine what manufacturer it is associated with.

The associated ID 1304 that is transmitted along with the routing information in primary routing information 904 is then compared with the profile database 1308 to determine if a profile associated therewith is available. This information is stored in a transaction database 1310 such that, at a later time, for each routing code received in the form of the information in primary routing information 904, there will associated therewith the IDs 1304 of each of the PCs 906. The associated profiles in database

1308, which are stored in association with IDs 1304, can then be assembled and transmitted to a subscriber as referenced by a subscriber node 1312 on the network 910. The ARS 308 can do this in two modes, a realtime mode or a non-realtime mode. In a realtime mode, each time a PC 906 accesses the advertiser database 310, that user's profile information is uploaded to the subscriber node 1312. At the same time, billing information is generated for that subscriber 1312 which is stored in a billing database 1316. Therefore, the ARS 308 has the ability to inform the subscriber 1312 of each transaction, bill for those transactions, and also provide to the subscriber 1312 profile information regarding who is accessing the particular product advertisement having associated therewith the routing information field 904 for a particular routing code as described hereinabove. This information, once assembled, can then be transmitted to the subscriber 1312 and also be reflected in billing information and stored in the billing information database 1316.

Referring now to FIGURE 14, there is illustrated a flowchart depicting the operation for storing the profile for the user. The program is initiated in a block 1402 and then proceeds to a function block 1404, wherein the system will prompt for the profile upon initiation of the system. This initiation is a function that is set to activate whenever the user initially loads the software that he or she is provided. The purpose for this is to create, in addition to the setup information, a user profile. Once the user is prompted for this, then the program will flow to a decision block 1406 to determine whether the user provides basic or detailed information. This is selectable by the user. If selecting basic, the program will flow to a function block 1408 wherein the user will enter basic information such as name and serial number and possibly an address. However, to provide some incentive to the user to enter more information, the original prompt in function block 1404 would have offers for such things as coupons, discounts, etc, if the user will enter additional information. If the user selects this option, the program from the decision block 1406 to a function block 1410. In the function block 1410, the user is prompted to enter specific information such as job, income level,

general family history, demographic information and more. There can be any amount of information collected in this particular function block.

Once all of the information is collected, in either the basic mode or the more specific mode, the program will then flow to a function block 1412 where this information is stored locally. The program then flows to a decision block 1414 to then go on-line to the host or the ARS 308. In general, the user is prompted to determine whether he or she wants to send this information to the host at the present time or to send it later. If he or she selects the "later" option, the program will flow to a function block 1415 to prompt the user at a later time to send the information. In the disclosed embodiment, the user will not be able to utilize the software until the profile information is sent to the host. Therefore, the user may have to activate this at a later time in order to connect with the host.

If the user has selected the option to upload the profile information to the host, the program will flow to the function block 1416 to initiate the connect process and then to a decision block 1418 to determine if the connection has been made. If not, the program will flow along a "N" path to a time to decision block 1420 which will time to an error block 1422 or back to the input of the connect decision block 1418. The program, once connected, will then flow along a "Y" path from decision block 1418 to a function block 1428 to send the profile information with the ID of the computer or user to the host. The ID is basically, as described hereinabove, a "cookie" in the computer which is accessed by the program when transmitting to the host. The program will then flow to a function block 1430 to activate the program such that it, at later time, can operate without requiring all of the set up information. In general, all of the operation of this flowchart is performed with a "wizard" which steps the user through the setup process. Once complete, the program will flow to a Done block 1432.

Referring now to FIGURE 15, there is illustrated a flowchart depicting the operation of the host when receiving a transaction. The program is initiated at a start block 1502 and then proceeds to decision block 1504, wherein it is determined whether the system has received a routing request, i.e., the routing information 904 in the form of a tone, etc., embedded in the audio signal as described hereinabove with respect to FIGURE 9. The program will loop back around to the input of decision block 1504 until the routing request has been received. At this time, the program will flow along the "Y" path to a function block 1506 to receive the primary routing information and the user ID. Essentially, this primary routing information is extracted from the audio tone, in addition to the user ID. The program then flows to a function block 1508 to look up the manufacturer URL that corresponds to the received primary routing information and then return the necessary command information to the originating PC 108 in order to allow that PC to connect to the destination associated with the primary routing information. Thereafter, the program will flow to a function block 1510 to update the transaction database 1310 for the current transaction. In general, the routing information 904 will be stored as a single field with the associated IDs. The profile database, as described hereinabove, has associated therewith detailed profiles of each user on the system that has activated their software in association with their ID. Since the ID was sent in association with the routing information, what is stored in the transaction database is the routing code, in association with all of the IDs transmitted to the system in association with that particular routing code. Once this transaction database has been updated, as described hereinabove, the transactions can be transferred back to the subscriber at node 312 with the detailed profile information from the profile database 1308.

The profile information can be transmitted back to the subscriber or manufacturer in the node 312 in realtime or non-realtime. A decision block 1512 is provided for this, which determines if the delivery is realtime. If realtime, the program will flow along a "Y" path to a function block 1514 wherein the information will be

immediately forwarded to the manufacturer or subscriber. The program will then flow to a function block 1516 wherein the billing for that particular manufacturer or subscriber will be updated in the billing database 1316. The program will then flow into an End block 1518. If it was non-realtime, the program moves along the "N" path to a function block 1520 wherein it is set for a later delivery and it is accrued in the transaction database. In any event, the transaction database will accrue all information associated with a particular routing code.

With a realtime transaction, it is possible for a manufacturer to place an ad in a magazine or to place a product on a shelf at a particular time. The manufacturer can thereafter monitor the times when either the ads are or the products are purchased. Of course, they must be scanned into a computer which will provide some delay. However, the manufacturer can gain a very current view of how a product is moving. For example, if a cola manufacturer were to provide a promotional advertisement on, for example, television, indicating that a new cola was going to be placed on the shelf and that the first 1000 purchasers, for example, scanning their code into the network would receive some benefit, such as a chance to win a trip to some famous resort in Florida or some other incentive, the manufacturer would have a very good idea as to how well the advertisement was received. Further, the advertiser would know where the receptive markets were. If this advertiser, for example, had placed the television advertisement in ten cities and received overwhelming response from one city, but very poor response from another city, he would then have some inclination to believe that either one poor response city was not a good market or that the advertising medium he had chosen was very poor. Since the advertiser can obtain a relatively instant response and also content with that response as to the demographics of the responder, very important information can be obtained in a relatively short time.

It should be noted that the disclosed embodiment is not limited to a single source PC 302, but may encompass a large number of source computers connected over

a global communication network. Additionally, the embodiment is not limited to a single ARS 308 or a single advertiser server 312, but may include a plurality of ARS and advertiser systems, indicated by the addition of ARS 314 and advertiser server A 316, respectively. It should also be noted that this embodiment is not limited only to global communication networks, but also may be used with LAN, WAN, and peer-to-peer configurations.

It should also be noted that the disclosed embodiment is not limited to a personal computer, but is also applicable to, for example, a Network Computer ("NetPC"), a scaled-down version of the PC, or any system which accommodates user interaction and interfaces to information resources.

One typical application of the above noted technique is for providing a triggering event during a program, such as a sport event. In a first example, this may be generated by an advertiser. One could imagine that, due to the cost of advertisements in a high profile sports program, there is a desire to utilize this time widely. If, for example, an advertiser contracted for 15 seconds worth of advertising time, they could insert within their program a tone containing the routing information. This routing information can then be output to the user's PC which will cause the user's PC to, via the network, obtain information from a remote location typically controlled by the advertiser. This could be in the form of an advertisement of a length longer than that contracted for. Further, this could be an interactive type of advertisement. An important aspect to the type of interaction between the actual broadcast program with the embedded routing information and the manufacturer's site is the fact that there is provided in the information as to the user's PC and a profile of the user themselves. Therefore, an advertiser can actually gain realtime information as to the number of individuals that are watching their particular advertisement and also information as to the background of those individuals, profile information, etc. This can be a very valuable asset to an advertiser.

In another example, the producer of the program, whether it be an on-air program, a program embedded in a video tape, CD-ROM, DVD, or a cassette, can allow the user to automatically access additional information that is not displayed on the screen. For example, in a sporting event, various statistics can be provided to the user from a remote location, merely by the viewer watching the program. When these statistics are provided, the advertiser can be provided with profile information and background information regarding the user. This can be important when, for example, the user may record a sports program. If the manufacturer sees that this program routing code is being output from some device at a later time than the actual broadcast itself, this allows the advertisers to actually see that their program is still being used and also what type of individual is using it. Alternatively, the broadcaster could determine the same and actually bill the advertiser an additional sum for a later broadcast. This is all due to the fact that the routing information automatically, through a PC and a network, will provide an indication to the advertiser for other intermediary regarding the time at which the actual information was broadcast.

The different type of medium that can be utilized with the above embodiment are such things as advertisements, which are discussed hereinabove, contests, games, news programs, education, coupon promotional programs, demonstration media (demos), photographs, all of which can be broadcast on a private site or a public site. This all will provide the ability to allow realtime interface with the network and the remote location for obtaining the routed information and also allow for realtime billing and accounting.

Referring now to FIGURE 16, there is illustrated a general block diagram of a disclosed embodiment. A bar code scanning wand 1600 is provided by a wand distributor to customers and is associated with that distributor via a wand ID stored therein. The wand 1600 is either sold or freely distributed to customers for use with their personal computing systems. Since more and more products are being sold using

bar codes, it can be appreciated that a user having the wand 1600 can scan bar codes of a multitude of products in order to obtain more information. Information about these products can be made immediately available to the user from the manufacturer for presentation by the user's computer 302. Beyond simply displaying information about the product in which the user is interested, the wand distributor may include additional advertising information for display to the user such as information about other promotions or products provided or sold by the wand distributor. Similarly, advertisers may provide catalogs of advertisements or information in newspapers or periodicals where the user simply scans the bar code associated with the advertisement using the wand 1600 to obtain further information. There is provided a paper source 1602 having contained thereon an advertisement 1604 and an associated bar code 1606. (Note that the disclosed concept is not limited to scanning of bar codes 1606 from paper sources 1602, but is also operable to scan a bar code 1606 on the product itself. Also, the wand 1600 can be any type of device that will scan any type of image having information encoded therein.) Further description of applications and operation of the bar code scanning wand 1600 and the use of the bar code information is found in pending U.S. Patent Application, Serial No. 09/151,471 filed on September 11, 1998 and entitled "METHOD FOR INTERFACING SCANNED PRODUCT INFORMATION WITH A SOURCE FOR THE PRODUCT OVER A GLOBAL NETWORK," which application is incorporated by reference in its entirety herein.

After obtaining the wand 1600 from the wand distributor, the user connects the wand 1600 to their PC 302. During a scanning operation, wand 1600 reads bar code data 1606 and the wand ID into a "wedge" interface 1608 for conversion into keyboard data, which keyboard data is passed therefrom into the keyboard input port of PC 302. The importance of the wand ID will be discussed in more detail hereinbelow.

The wedge interface 1608 is simply an interface box containing circuitry that accommodates inputs from both the scanning wand 1600 and a computer keyboard

1610. This merely allows the information scanned by the wand 1600 to be input into the PC302. In the disclosed embodiment, the wedge interface 1608 will convert any information. The data output from the wand 1600 is passed into the wedge interface 1608 for conversion into keyboard data which is readily recognizable by the PC 302. Therefore, the wand 1600 is not required to be connected to a separate port on the PC 302. This data is recognized as a sequence of keystrokes. However, the output of the wand 1600 can be input in any manner compatible with the PC 302. When not receiving scanner data, the wedge interface 1608 simply acts as a pass-through device for keyboard data from the keyboard 1610. In any case, the information is ultimately processed by a processor in the PC 302 and can be presented to the user on a display 1612. The wedge interface is operable to provide a decoding function for the bar code and conversion thereof to keystroke input data.

In operation, the product code of a product is provided in the form of a bar code 1606. This bar code 1606 is the “link” to a product. The disclosed embodiment is operable to connect that product information contained in the bar code 1606 with a web page of the manufacturer of that product by utilizing the bar code 1606 as the product “identifier.” The program operating on the PC 302 provides routing information to the ARS 308 after launching the browser on the PC 302 and connecting to the ARS 308 over the GCN 306, which ARS 308 then performs the necessary steps to cause the browser to connect to the manufacturer web site, while also providing for an accounting step, as will be described in more detail hereinbelow.

The bar code 1606 by itself is incompatible with any kind of network for the purposes of communication therewith. It is primarily provided for a retail-type setting. Therefore, the information contained in the bar code 1606, by itself, does not allow for anything other than identification of a product, assuming that one has a database 1614 containing information as to a correlation between the product and the bar code 1606.

The wedge interface 1608 is operable to decode the bar code 1606 to extract the encoded information therein, and append to that decoded bar code information relating to an ID for the wand 1600. This information is then forwarded to the ARS by the resident program in the PC 302. This is facilitated by intermediate routing information stored in the program indicating to which node on the GCN 306 the scanned bar code information is to be sent, i.e., to the ARS 308. It is important to note that the information in the bar code 1606 must be converted from its optical image to numerical values which are then ultimately input to the keyboard input port of PC 302 and converted into data compatible with communication software residing on the PC 302 (in this case, HTML language for insertion into a browser program). When the scanned information is input to the PC 302, the resident program launches the browser program and then assembles a communication packet comprised of the URL of the ARS 308, the wand ID and the user ID. If another type of communications program were utilized, then it would have to be converted into language compatible with that program. Of course, a user could actually key in the information on the bar code 102 and then append the appropriate intermediate routing information thereafter. As will be described hereinbelow, the intermediate routing information appended thereto is the URL of the ARS 308 disposed on the GCN 306.

As part of the configuration for using the wand 1600, the PC 302 hosts wand software which is operable to interpret data transmitted from the wand 1600, and to create a message packet having the scanned product information and wand ID, routing information, and a user ID which identifies the user location of the wand 1600. The wand software loads at boot-up of the PC 302 and runs in the background. In response to receiving a scanned bar code 1606, the wedge interface outputs a keystroke code (e.g., ALT-F10) to bring the wand program into the foreground for interaction by the operating system. The wand program then inserts the necessary information into the browser program. The message packet is then transmitted to interface 304 across the global communication network 306 to the ARS 308. The ARS 308 interrogates the

message packet and performs a lookup function using the ARS database 310. If a match is found between particular parameters of the message packet, a return message packet is sent back to the PC 302 for processing.

5 The wand program running on PC 302 functions to partition the browser window displayed to the user into several individual areas. This is for the purpose of preparing to present to the user selected information in each of the individual areas (also called “framing”). The selected information comprises the product information which the user requested by scanning the bar code 1606 using the wand 1600, information about the wand distributor which establishes the identity of the company associated with that particular wand 1600, and at least one or more other frames which may be advertisements related to other products that the wand distributor sells. Note that the advertisements displayed by the wand distributor may be related to the product of interest or totally unrelated. For example, if a user scans the bar code 1606 of a Company A soda, the wand distributor may generate an advertisement of a new soft drink being marketed by Company A, that it sells. On the other hand, the wand distributor may also structure the display of information to the user such that a user requesting product information of a Product X may get the requested information of Product X along with advertisements for a competing item Product Y. Essentially, the wand distributor is free to generate any advertisement to the user in response to the user requesting product information.

20 The return message packet transmitted from the ARS 308 to the PC 302 is then transmitted back across the GCN 306 to the advertiser server 312. The advertiser server 312 restructures the message packet and appends the particular product information for transmission back to the PC 302. Upon receiving the particular advertiser information from advertiser server 312, the PC 302 then retransmits a message to the wand distributor site 1616 and E-commerce site 1618 to obtain the information that needs to be framed in the browser window displayed to the user.

Therefore, the wand 1600 is associated with the wand distributor by way of a wand ID such that scanning a product bar code 1606 in order to obtain information about that particular product generates one or more responses from one or more remote sites disposed on the GCN 306. Stored in the wand 1600 is the wand ID which
5 establishes its relationship to the wand distributor. Proprietary wand software running on the PC 302 operates to decode scanned bar code information and the wand ID received from the wand 1600 and wedge interface 1608, and also provides a unique user ID for establishing the location of the user of the wand 1600. The wand software also assembles message packets and works in conjunction with the on-board communication
10 software (e.g., a browser) to automatically route the message packets across the GCN 306 such that the one or more remote sites disposed on the GCN 306 return information to be framed for presentation to the user.

Referring now to FIGURE 16a, there is illustrated an addition to the flowchart of FIGURE 14 for registering an input device, for one embodiment of the disclosure, with the ARS 308 in conjunction with a user ID. As described hereinabove, each user,
15 when they generated their user profile when first contacting the ARS 308 to activate their software, defines a user ID for storage in their PC resident software. This user ID, as also described hereinabove, is utilized to identify the PC 302 to the ARS 308 whenever making a transaction. This is utilized for, among other things, updating
20 profile information in the database 310. However, when an input device, such as the input device in the form of a wand 1600, is utilized, there are a number of ways to identify this wand 1600. One can be with the use of a unique wand ID associated with the wand 1600, as will be described hereinbelow. The other is to create a wand ID in the software program operating in the PC 302 running the PC resident background
25 program as described hereinabove. In a situation where the ID is created in the program, reference is made to block 1410 of FIGURE 14 and subsequent thereto. After the user has entered very specific information, jobs, history and demographics, etc., the system will then prompt the individual for information regarding the input device, as

indicated by a function block 1630. This prompt will basically inquire as to whether the user has an input device for reading machine readable code or for sensing audible signals. It may desire to know whether the user has received an audible code from a broadcast system such as a TV, or the wand 1600 is being utilized to scan machine readable code in the form of a bar code. The program block will then flow to a function block 1632 wherein various input device types are presented to the user on their display returned over the network 306 from the ARS 308, and then the user selects which type of input device is attached to their computer. For example, it might be a scanning wand, it might be an audio input device, or any other type of device that allows for input of information. For example, it is conceivable that the unique wand ID is that of some type of tool being utilized in conjunction with the program as an input device. The unique wand ID could even be the idea of a disk drive wherein the wand ID would be generalized as a tool ID.

Once the type of input device is input, then the prompt will query what type of device is attached, such as the type of scanning wand 1600. The system will then ask for the distributor of the wand 1600. Of course, as described hereinabove, the wand 1600 could have embedded therein a unique wand ID which would remove the need for inputting the distributor, as the ARS 308 will recognize this particular wand ID. However, in the situation wherein the wand ID is not disposed within the wand 1600, then the user will have to view the wand or tool 1600 to determine the distributor thereof. This is what input information would then be noted in the user profile in the ARS 308. This allows the ARS 308, at a later time, to match up the user ID, requiring no other user ID, with their user profile to determine what distributor distributed their wand 1600, such that information can be returned associated with that distributor, as will be described hereinbelow. Therefore, the combination of a user ID and a corresponding entry in the database of the ARS 308 will constitute the wand ID or tool ID.

Referring now to FIGURE 17, there is illustrated a conversion circuit of the wedge interface. A microcontroller 1700 provides conversion of the data from the wand 1600 and controls interfacing of the keyboard 1610 and wand 1600 with the PC 302. The microcontroller 1700 has contained therein a memory 1702 for storing a wand ID (or even a URL for some applications) or it can have external memory. There are provided a plurality of wand interfaces 1704 to the wand 1600, a plurality of PC interfaces 1706 to the PC 302, and plurality of keyboard interfaces 1708 to the keyboard 106. In general, the wand interfaces 1704 comprise a serial data line, a ground line, and a power line. Similarly, the keyboard interfaces 1708 comprise a serial data line, a ground line, a clock line, and a power line. The PC 302 provides a clock line, a power line, a serial data, and a ground line for input to the microcontroller 1700. The microcontroller 1700 is operable to receive signals from the keyboard 1610 and transfer the signals to the PC 302 as keyboard signals. Operation with the keyboard 1610 is essentially a "pass-through" procedure. Data output from the keyboard 1610 is already in keyboard format, and therefore requires no conversion by the wedge interface 1608. With respect to the wand 1600, the serial data is not compatible with a keyboard 1610 and, therefore, it must be converted into a keyboard format in order to allow input thereof to the keyboard input of the PC 302.

The microcontroller 1700 performs the conversion function after decoding this bar code information, and conversion of this bar code information into an appropriate stream of data which is comprised of the bar code information and the appended wand ID (or even a URL in some applications). This appended wand ID (and/or URL) will be pre-stored in the memory 1702 and is programmable at the time of manufacture. It is noted that the memory 1702 is illustrated as being contained within the microcontroller 1702 to provide a single chip solution. However, this could be external memory that is accessible by the microcontroller 1702. Therefore, the microcontroller 1700 provides an interface between the wand 1600 and the keyboard 1610 to the PC 302 which allows the wand 1600 to receive coded information and convert it to

keyboard strokes or, alternatively, to merely pass-through the keystrokes from the keyboard 1610. Therefore, the user need not install any type of plug-in circuit board into the motherboard of the PC 302 in order to provide an interface to the wand 1600; rather, the user need only utilize the already available keyboard port in order to input the appropriate data into the system.

In this particular disclosed embodiment, the microcontroller 1700 comprises a PIC16C73 microcontroller by *Microchip Technologies*TM. The PIC16C73 device is a low cost CMOS 8-bit microcontroller with an integrated analog-to-digital converter. The PIC16C73 device, as illustrated in the disclosed embodiment, has 192 bytes of RAM and 4k x 4 of EPROM memory. The microcontroller 1700 can accommodate asynchronous or synchronous inputs from input devices connected to it. In this disclosed embodiment, communication to the keyboard 1610 is synchronous while it is asynchronous when communicating with wand 1600.

It should be noted that, although in this particular embodiment bar code information of the bar code 1606 is input into the keyboard input port of the PC 302, disclosed methods may also be advantageously utilized with high speed port architectures such as Universal Serial Bus ("USB") and IEEE 1394.

Bar codes are structured to be read in either direction. Timing considerations need to be addressed because of the variety of individuals scanning the bar code introduce a wide variety of scan rates. Bar codes use bars of varying widths. The presence of a black bar generates a positive pulse, and the absence of a black bar generates no pulse. Each character of a conventional bar code has associated therewith seven pulses or bars. Depending on the width of the bars, the time between pulses varies. In this disclosed embodiment, the interface circuitry 1608 performs a "running" calculation of the scan time based upon the rising edge of the pulses commencing with the leader or header information. The minimum and maximum scans times are

calculated continuously in software with the interface 1608 during the scanning process to ensure a successful scan by the user.

Referring now to FIGURE 18, there is illustrated a sample message packet transmitted from the user's PC 302 to the ARS. The message packet 1800 comprises a number of bits of information including the bar code information 1802 obtained from the user scanning the bar code with the wand 1600; the wand ID 1804 which is embedded in a memory in the wand 1600 and identifies it with a particular wand distributor; and a user ID 1806 which is derived from the software running on the PC 302 and which identifies uniquely with the user location. Note that the message packet includes other necessary information for the proper transmission for point to point.

Referring now to FIGURE 19, there is illustrated a more detailed block diagram of the routing of the message packets in order to present the framed information to the user. As is mentioned hereinabove, when the user scans a bar code 1606 using the wand 1600, a wand program running on the user PC 302 is operable to interpret the information output by the wand 1600 and generate a message packet for transmission over the GCN 306. The wand program assembles the message packet such that it is directed to the ARS 308 disposed on the GCN 306. The message packet contains several pieces of information including the wand ID 1804 which links it to the wand distributor, the user ID 1806 which identifies the particular user using the wand 1600, and bar code information describing a particular product of interest to the user. This message from the PC 302 is transmitted over a path 1900 to the ARS 308 where the ARS database 310 is accessed to cross reference the ID information and bar code information to a particular advertiser and wand distributor. The ARS 308 returns a message packet over a path 1902 to the user PC 302 which contains routing information as to the location of various other sites disposed on the GCN 306, for example, the advertiser server 312 and wand distributor site 1616.

It is noted that, when the wand (or tool) is utilized, the program at the PC may recognize this and merely input the user ID in the want (or tool) ID field. Alternatively, the mere receipt of a user ID in association with product code information will trigger the ARS 308 to assume that the wand 1600 was utilized. It is only important that the use of the wand (or tool) be recognized and that the user's PC be routed to a location on the network preassociated with that wand (or tool) distributor. Further, it is the routing of the user's PC to a predetermined location on the network based upon the use of a particular tool, a particular type of tool or a general class of tools that elicits the connection. For example, it would be that the network connection is made in response to the user utilizing a bar code scanner. This would connect the user to a website for a general bar code scanner tool. For a disk drive, the program would recognize that a disk drive had been installed (or merely used) and then route the user to the website of the disk drive manufacturer, a competitor of such or even to some marketing firm that wants to contact individuals that use or initiate such a piece of equipment.

It can be appreciated that other information can also be provided by the ARS 308 which more closely targets the particular user of the wand 1600. For example, if it is known that a particular wand 1600 is sold in a certain geographic area, this information can be useful in targeting the particular user with certain advertising information relevant to that geographic area. In any case, the information returned from the ARS 308 over path 1902 provides enough information for the wand program running on the user PC 302 to identify a number of other sites disposed on the GCN 306. The user PC 302 then processes the return message packet and routes another message packet over a path 1904 to the advertiser server 312. The advertiser server 312 then returns product information of the particular product in which the user was interested back to the user PC 302 over a path 1906. Similarly, the user PC 302 routes information (e.g., the URL of the wand distributor site and the user profile) to the wand distributor site 1616 over a path 1908 in order to obtain information back over a path 1910 for framing any banners which identify the wand distributor. Additionally, the

user PC 302 forwards a message packet to the E-commerce site 1618 over a path 1912 in order to return information regarding any particular advertisements the wand distributor wants to display to the user. The advertisements are returned to the PC 302 over a path 1914.

5 Referring now to FIGURE 20, there is illustrated a block diagram of a browser window according to the disclosed embodiment. The browser window 2000 is partitioned into a plurality of areas for framing specific information. A bar code area 2002 displays that product information in which the user was interested; a wand specific area 2004 displays information about the wand distributor; and an E-commerce
10 area 2006 displays advertising information that the wand distributor selects for display according to this particular user and wand 1600. As mentioned hereinabove, a program operable to process scanned bar code information with the unique wand 1600 develops the browser window by partitioning it into specific areas for the framing of information. Therefore, information returned from the E-commerce site 1608 is passed through the
15 GCN 306 to the particular E-commerce frame 2006. Similarly, information about the particular product of interest is returned from the advertiser site 312 across the GCN 306 to the particular bar code specific area 2002. Information placed in the wand specific area 2004 is information about the wand distributor which is returned from the wand distributor site 1616 across GCN 306.

20 Referring now to FIGURE 21, there is illustrated a structure of information contained in the ARS database. The ARS database 310 contains a variety of information required to properly interrogate and assemble packets for obtaining information from the various sites disposed on the GCN 306. The ARS database 310 has a database structure 2100 which contains addresses for the web sites containing the
25 product information requested by the user when scanning the bar code 1606 with the wand 1600. Under a product heading 2102 are listed the particular bar codes and associated routing information for addressing the respective server location. For

example, the ARS server 308 may contain any number of advertisers having unique URL addresses associated therewith. Therefore, the bar code 1606 of a particular product is associated with a unique URL address which routes any request for information of that product to that particular advertiser's site. Also part of the ARS database structure 2000 is a heading of wand under which is the wand ID 1804 and the distributor associated with that wand ID 1804.

It can be appreciated that there may be a number of distributors using the disclosed architecture such that each distributor has an ID embedded in the wand which uniquely identifies that wand with the particular distributor. Therefore, the unique wand ID 1804 needs to be listed with the respective distributors of that wand 1600 in order to process the information that needs to be framed and displayed to that particular user. Another heading under the ARS database structure 2100 is a user heading 2106 which contains profile information associated with that particular user ID 1806. As mentioned hereinabove, the user ID 1806 is obtained via the wand software running on the PC 302 and upon installation or subsequent configuration may request that the user input certain profile information which may be used to target that particular user with products and services which identify with that user profile. The ARS database structure 2100 also contains an E-commerce heading 2108 which contains information related to the bar code 1606 and an advertisement that may be triggered by the request for that information. For example, any bar code 1606 associated with a paper source 1600 can be associated with the specific information in the ARS database 310. A user wishing to obtain information about a specific soft drink may, in fact, trigger an advertising response of a competitor product. Similarly, the user interested in information about that particular soft drink may also trigger information which is relevant to that particular product or a product which may normally be served in conjunction with that soft drink. Furthermore, if the user profile indicates that this individual has significant interest in finance or insurance, the request for information regarding this particular bar coded product may trigger advertisement from an E-commerce server 1618 related to

information about finance and insurance. It should be noted that the information described as contained within the ARS database structure 2100 is not limited to what has been described, but may comprise any number of pieces of information used to present desired information to the computer display of the user.

5 Referring now to FIGURE 22, there is illustrated a flowchart of the process of receiving information from the user's perspective, and according to the disclosed embodiment. The wand software running on the user's PC 302 runs in the background until activated by output from the wand 1600. Therefore, flow moves to a decision block 2200 where if a scanned input does not occur, flow moves out the "N" path and
10 loops back to the input of decision block 2200. On the other hand, if scanned input information is received, flow moves out the "Y" path to a function block 2202 where the wand software assembles a message packet containing the bar code information, the wand ID 1804 and the ARS 308 URL address. Additionally, the browser is launched in which this information is placed for transmission to the ARS 308. Flow then moves to
15 a function block 2204 where the browser is partitioned into any number of areas in which information is displayed when obtained from the wand distributor site 1616, the E-commerce site 1618, and the advertiser server 312. It should be known that although three frames are shown in the particular window 2000 of this embodiment, the number of frames displayed in the window 2000 is limited only by the available real estate of
20 the window 2000 area itself.

After the wand software partitions the browser window into one or more frames in preparation of receipt of return information, flow moves to a decision block 2206 where the computer waits for information to be returned from the various sites disposed on the GCN 306. If information is not returned, flow moves out the "N" path and
25 simply loops back to the input to continue monitoring for receipt of the information. If information has been received, flow moves out the "Y" path to a function block 2208 where routing information for each frame (or partitioned area of the window 2000) is

inserted into one or more packets for transmission to the various sites. The various sites then return the requested information back to the PC 302, as indicated in function block 2210. Flow is then to a function block 2212 where the proprietary software working in conjunction with the hosted browser places the returned information into the respective frames of the window. The user, viewing the display at PC 302, then perceives a variety of information, one of which is the particular product information which he or she requested, in addition to wand distributor information, and possibly other advertisements based upon the user's profile.

Referring now to FIGURE 23, there is illustrated a flowchart of the process according to the ARS. The ARS 308 is operable to decode and process message received from the GCN 306. Therefore, flow is to a decision block 2300 where, if bar code information is not received, flow is out the "N" path with loop-back to its input. If bar code information has been received, flow is to a function block 2302 where a matching process occurs to link the bar-coded product information to its respective manufacturer. The ARS database 310 also associates the URL address of the manufacturer's server. When a match is found, the ARS 308 begins to assemble a message packet of information for transmission back to the PC 302, as indicated in function block 2304. The message packet contains the product information and the URL address of the manufacturer's website. Flow then moves to a decision block 2306 where the wand ID 1804 is compared with the list of wand IDs issued by the particular wand distributor. If the wand ID 1804 is validated, flow moves out the "Y" path to a function block 2308 where the message packet is appended with the wand ID 1804 and distributor routing address. Flow then moves to a decision block 2310 where the ARS 308 determines if any E-commerce information is to be associated with a particular wand ID 1804. If so, flow is out the "Y" path to a function block 2312 where the message packet is appended with the E-commerce routing string. The E-commerce routing string provides addressing for the E-commerce server 1618. Flow then moves

to a function block 2314 where all message packets are returned back to the PC 302 for processing.

Referring back to decision block 2306, if the wand ID 1804 is determined to be invalid, flow moves out the “N” path and jumps forward to the input of decision block 2314, since the lack of a wand ID 1804 interrupts the link to any advertising provided by the E-commerce server 1618. At this point, the only information provided is the link to the adverse server 312 for return of product information. Referring now to decision block 2310, if no E-commerce information is available, flow moves out the “N” path and jumps forward to the input of function block 2314 where the message packet back to the PC 302 contains only the URL of the advertiser server 312, the bar code information, the distributor server 1616 address and wand ID 1804 information.

Referring now to FIGURE 24, there is illustrated a flowchart of the process performed at the E-commerce site. The E-commerce server 1618 receives the message packet from the user PC 302, as indicated in function block 2400, and decodes the packet to perform a match with the bar coded information. Moving on to a decision block 2402, if the match is unsuccessful, flow is out the “N” path to a function block 2404 where the match is rejected. A message may be returned to indicate that a problem occurred and the user may need to re-scan the product bar code 1606. If a successful match occurs, flow moves out the “Y” path to a function block 2406 where the wand ID 1804 is matched with the bar code product information. The bar coded information may be distributed to customers over a large geographic area. However, the wand 1606 may be coded for certain geographic areas. For example, a wand 1600 having an XXX ID may be restricted for sale in the Southwestern United States while a wand 1600 having a YYY ID may be sold only in the Northeast. In this way, geographic areas may be targeted with advertising more appealing to that particular area. Advertising returned to the user PC 302 may be focused further by obtaining a user profile when the software or wand 1600 are installed. In this way, advertising may

be focused based upon the user profile. Therefore, flow moves to a function block 2408 to lookup the E-commerce action based upon the wand ID 1804 and the bar code information. Flow moves to a function block 2410 to assemble all the information into a packet for return to the user PC 302. The product information and/or user profile information may be returned. Flow is then to a function block 2412 where the message packet is transmitted.

FIGURE 25a illustrates a bar code 2502 which can be scanned with the wand 1600 to extract the information contained therein. Typically, these bar codes are associated with a product or a service and they will have the decoded information disposed thereunder in the form of numbers, this represented by a series of "xxx's." These bar codes are conventional and can be generated with many types of programs. However, they are usually uniquely associated with a given product or product UPN or they can be generated for any type of application a user desires them for. However, with a UPN, they have specific links and specific fields. For example, a certain portion of the bar code 2502 when associated with a product having a UPN, this portion will define the company. Therefore, all UPNs for a given company will have this set portion and it will always be the same.

The bar code 2502 is disposed on a surface, either the surface of a product or even an advertisement or a tag associated with the product. It is typically in close association with that product or service. On the surface in proximity thereto is provided a logo 2504. This logo is an indicia of the fact that the bar code 2502 is associated with the system described hereinabove, i.e., when this bar code 2502 is scanned with the PC 302 running the appropriate software, this indicates that information is in the database of the ARS 308. Of course, the user does not know that this information must first be obtained from ARS 308; rather, the user merely knows that the indicia 2504 indicates that scanning of the bar code 2502 will launch a computer to a destination site. This is unique in that the bar code performs two

functions, a retail function and a routing function. However, the user, when selecting products, will have no idea that this bar code 2502 on the product can actually allow them to have access to a defined location on the network without the indicia 2504.

Referring now to FIGURE 25b, there is illustrated an alternate embodiment, wherein the bar code 2502 is surrounded by a border 2506, which border 2506 can be a particular color that can stand out. Typically, this bar code 2502 will be disposed on a product on a retail shelf. When the consumer picks up the product, the consumer can actually determine which products have a product code for use by the retailer that is also useful to access some location on the network. For example, a manufacturer may want to offer some type of prize or incentive for an individual to purchase their product. They could actually offer some type of coupon from the remote location, provided that a consumer purchases their product and then scans it with the wand 1600 attached to the PC. If this occurs, then the user will be connected to the location and receive some type of coupon. However, in order for this to occur, the user must recognize that the product they are purchasing was one that had a UPN associated therewith that was “network compatible.” This network compatibility indicates to the consumer that they can in fact access some location over the network. They are not informed as to what location can be located; rather, only that some type of particular location can be located. This provides a means by which the manufacturer can possibly sell more product and various types of coupons that can be uploaded.

Referring now to FIGURE 26, there is illustrated a block diagram of an alternate embodiment of a system for facilitating access to a location on a network. A presentation source 2600 is provided having both a visual aspect 2602 and a sound aspect 2604. This, as described hereinabove, can be facilitated by the embodiment of FIGURE 1. The presentation source 2600 may provide an audio visual presentation or a communication having audio and visual content. The presentation provided by presentation source 2600 may be broadcast or it may be live. The visual aspect 2602

and the sound aspect 2604 may appear together or separately or in various sequences or combinations. The visual aspect 2602 may include both program material or visual cues indicative of a particular relationship or action or a visually perceivable control signal. Similarly, the sound aspect 2604 may include program material, or audible cues indicative of a particular relationship or action or it may include a control signal.

Continuing further with FIGURE 26, there is shown a computer 2606 having an input device 207 and a block representing a consumer 2608 wherein the computer 2606 and the consumer 2608 are linked by an interaction link 2612. The computer 2606 and the consumer 2608 are further linked with the visual aspect 2602 and the sound aspect 2604 of the presentation source 2600 by a perception link 2610 shown between the respective blocks by dashed line paths indicating generally a wireless link over which occur the perception of the individual aspects of the presentation by one or both of the computer 2606 and the consumer 2608. In some cases a portion of the perception link 2610 may be a coupling other than wireless. There is further shown coupled with the computer 2606 a network 2614 linked by a bidirectional communication channel 2616. The network 2614 is also coupled to a location on the network 2618 via a bidirectional communication link 2620. In the disclosed embodiment, the network 2618 is the GCN 306.

In operation, a presentation provided by a presentation source 2600, i.e., a broadcast station, which may have both visual and sound aspects is perceived by the computer and/or the consumer. Visual aspects, such as visual cues, and sound aspects, such as audible cues or control signals, may be perceived by either the consumer 2608 or the computer 2606 to call attention to a particular program element in the presentation or associated with the presentation or to a control action that is taking place or is enabled to take place depending upon the response of the computer 2606 or the consumer 2608. For example, during a program segment, a visual cue may appear to the consumer 2608 in association with an audible control or launching signal, which

together alert the consumer that a control action is occurring, such as establishing access to a location on the network in response to the launching signal. The computer 2606 may include an input device 2607 responsive to the launching signal. The output of the input device 2607 is processed by the computer under the control of a program
5 resident on the computer for establishing a connection via the network 2614 to the location on the network 2618 via the bidirectional communication channel 2620. The foregoing example is illustrative only and represents many possible variations in the operation of such a system. Visual aspect 2602 and the sound aspect 2604 are both provided, in an illustrative embodiment shown in FIGURE 26a, by a broadcast source
10 that broadcasts a program with the various cues and control signals embedded therein. A monitor 2620 of either a computer or a television is provided for receiving the broadcast. It should be understood that televisions, operating on an NTSC format, could be utilized separate and apart from the computer 2606. However, it should be understood that the computer 2606 could include as a portion thereof the ability to
15 receive a broadcast and display that broadcast. However, in this embodiment, a separate monitor or TV 2620 is illustrated.

Continuing with FIGURE 26a, the television 2620 is operable to receive on an antenna 2622 the broadcast. This is then displayed on a main display portion 2624. This is provided for a viewer 2626 to have the ability to view the program.
20 Additionally, there is provided a speaker 2628 for providing an audio output. This audio output can be provided to the user and also to the computer 2606 through a microphone 2630, which comprises the input device 2607. However, as described hereinabove, it should be understood that a direct connection between the computer 2606 and the TV 2620 could be provided for receiving the signal. Further, also
25 illustrated as an audible signal, the control signal could be a digital signal that is encoded within the Vertical Blanking Interval (VBI), a conventional technique for providing control information such as closed captioned programming.

During the broadcast, it may be desirable for an advertiser or the such to control the computer 2606 to interconnect with the remote location 2618 on the network 2614. When this occurs, a control signal will be provided to the computer, be that audible, as in the disclosed embodiment, or inaudible. This will enable the computer to link to the remote location 2618 and retrieve information therefrom for display on a computer display 2630. However, it should be understood that any action taken by the computer 2606 in response to receiving the control information via information received from the network could be anticipated. For example, the control information could control a user device such as a toy. Although not illustrated, the actions of this toy could actually be manipulated by the control signal.

In the illustrated embodiment, the information that is retrieved is displayed on the display 2630. However, in conjunction with the audible tone, which is perceptible by the user, there is also provided by video cue 2632. This video cue operates in a number of different manners, as will be described hereinbelow. This cue 2632 could occur prior to the audible tone or after the audible tone or in conjunction with the audible tone. The reason for this is that the audible tone may be masked by the audio portion of the broadcast. If the viewer 2626 is viewing the broadcast on the main display 2624, the viewer will see the cue 2632, this being a distinctive cue, appear. When the viewer 2626 sees the cue 2632 appear, the viewer 2626 will recognize that this cue 2632 is associated with some action that is being taken. In the illustrated embodiment, this is the presence of relevant information being displayed on the computer display 2630. This will cause the viewer 2626 to view the computer display 2630, as illustrated in phantom. It is noted that the audible portion of the program could be made distinctive enough to allow the user to view the display 2630. This is described in U.S. Patent Application Serial No. 09/489,879, entitled "METHOD AND APPARATUS FOR UTILIZING AN AUDIBLY CODED SIGNAL TO CONDUCT

COMMERCE OVER THE INTERNET”(Atty. Dkt. No. PHLY-24,918), which is incorporated herein by reference.

Referring now to FIGURE 27, there is illustrated one possible embodiment of a visual cue which may appear among the visual aspects 2602 of a presentation that is provided in the embodiment illustrated in FIGURE 26, this being the visual cue 2632. The visual cue 2700 of FIGURE 27 includes a stylized alphanumeric character or logo 2702. The logo 2702 in FIGURE 27 is accompanied by a mark of punctuation represented by the dot 2704 and the dot 2706, which mark of punctuation occurs in conjunction with the logo 2702, together providing a visual cue. In the detailed description to follow, this visual cue will be illustrated in several embodiments which enhance the visual impact of the visual cue of FIGURE 27.

Referring now to FIGURES 28a, 28b and 28c, there is illustrated an animation sequence in three cells involving a visual cue as illustrated in FIGURE 27. In FIGURE 28a is shown a stylized letter C 2802 having a circular portion 2804 disposed on the upper extremity of the character 2802. FIGURE 28b shows the same character 2802 having the same circular portion 2804 in conjunction with the detachment, from the character 2802, of a second circular portion 2806 which is caused to move along a path 2808 to a position 2810 to the left of the character 2802. FIGURE 28c illustrates the same character 2802 accompanied by the separation of the circular portion 2806 (which resided in position 2810) into circular portion 2812 and circular portion 2814. The circular portions 2812, 2814 are seen to move upward and downward respectively from position 2810 into new positions corresponding to a punctuation mark (colon) disposed to the left and adjacent the character 2802. FIGURES 28a, 28b and 28c illustrate the motion of a portion of a character or visual cue to form a new version of the visual cue in a way that attracts attention to itself through the successive movement of the respective portion of the character. Thus a colon is formed to the left of the character 2802 by moving a circular portion away from one part of the character 2802 along a

designated path to a position from which it may be further moved to complete the modification to the visual cue. It will be appreciated that the sequence illustrated in FIGURES 28a, 28b and 28c represent just one of many possible sequences which may be conceived and arranged for the same purpose. It will also be appreciated that visual cues are not limited to alphanumeric characters but may include any kind of visual image such as an icon, cartoon, logo or other symbol which may be manipulated in a manner similar to that illustrated in FIGURES 28a, 28b and 28c.

Referring now to FIGURES 29a, 29b and 29c there is illustrated an alternate animation sequence 2900 which begins with a character 2902 shown in FIGURE 29a. This character 2902 is accompanied by a single circular portion 2904 disposed to the left of the character 2902. The visual cue in FIGURE 29b shows the circular portion 2904 being separated into two circular portions 2906 and 2908 moving in respectively upward and downward directions to new positions as illustrated in FIGURE 29c, the new positions being 2910 and 2912 representing a punctuation mark (colon) disposed to the left of the character 2902. It will be appreciated that in the embodiment of FIGURES 29a, 29b and 29c as well as the embodiments previously described hereinabove that the animation of portions of the visual cue may be accompanied by various sound aspects depending on the program content of the presentation.

Referring now to FIGURE 30, there is illustrated a flowchart of one embodiment of the operation of the system of FIGURE 26, for facilitating access to a location on a network. The flow begins at the Start block 3000 and proceeds to a block 3002 representing the active presentation of a program capable of both visual and sound aspects, which program is provided by the presentation source 2600 as illustrated in FIGURE 26. Continuing with FIGURE 30, the flow proceeds to a decision block 3004 wherein a determination is made whether it is intended to release a launch signal to provide for a control action before providing a visual cue from the presentation. If the determination is negative, the flow proceeds to block 3006 where the system presents

the visual cue during the presentation of the program. If, however, it was intended to release the launch signal, that is, to release a control signal for the purpose of launching an application on the computer 2606 to establish a connection via the network 2614 to a location on the network 2618, then the flow follows the Y path to block 3008. In block 3008, the system releases the launch signal and the flow proceeds to a decision block 3010. In decision block 3010, a determination is made whether a visual cue was presented and, if the result of the determination is affirmative, then the flow proceeds to a next decision block 3014. If however, a visual cue was not presented previously, then the flow proceeds from decision block 3010 along the N path to a block 3012 where the visual cue is presented by the presentation source and the flow proceeds to decision block 3014. In decision block 3014, a determination is made as to whether animation of the visual cue has been requested and if the result of that determination is affirmative, then the flow follows the Y path to block 3016 wherein the animation sequence is performed on the visual cue. Following the completion of the animation sequence, the flow returns to the input to a block 3018. If however, an animation sequence was not requested for the visual cue, then the flow follows the N path from decision block 3014 to the input to block 3018 wherein the input device of the computer reads the launch signal released during the presentation. The flow proceeds to block 3020 where the application is launched on the computer 2606 to establish a connection on the network 2614. The access to the location 2618 on the network 2614 is performed in accordance with the application in block 3022. Once the connection is established, the routine of FIGURE 30 ends at block 3024.

It will be appreciated by persons skilled in the art that the flow chart of FIGURE 30 generally illustrates a process by which visual and/or sound aspects of a presentation may be utilized to call attention to and to launch an application which provides for access to a location on a network via a computer associated with the presentation containing the visual and/or sound aspects. FIGURE 30 illustrates several variations that are possible such as inverting the order of the visual aspect or the sound aspect that

is involved in the action to facilitate the access to a location on a network. Further, the providing of the visual cue and the release of the launch signal may occur substantially simultaneously, within a predetermined interval of time or in sequence, one after the other. Further, the launch signal, typically in the disclosed embodiment an audible sound, may be configured by its frequency or amplitude to be inaudible to human hearing but which may be detected by an input device on the computer of appropriate capability. Another variation is the animation of all or a portion of the visual cue with or without an associated corresponding sound aspect to enhance the attractability of the visual aspect and/or the sound aspect to a consumer who is present during the presentation and is desirous of establishing the aforementioned access to a location on a network, i.e., viewing the computer display. As mentioned hereinabove, the visual cue may take many forms including alphanumeric characters or icons, cartoons or other kinds of symbols or logos that are appropriate to the presentation being made by the presentation source and/or the particular action that is to result from the launch of the application on the computer in the system of FIGURE 26.

In addition to the above-noted axis, it is noted that the cue 2632 could be further animated by allowing it to traverse the screen. For example, the visible cue could be animated as “hopping” across the screen to the lower right-hand corner. This is something that will be a perceptible difference in the broadcast that would alert the user to the fact that some control action were being undertaken and they were to view the results of that control action.

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

1. A method for facilitating computer based access to a location on a network by a consumer witnessing a presentation, comprising the steps of:

5 providing a visual cue during the presentation apparent to the consumer and indicative of a relationship between the visual cue and the presence of the location on the network; and

releasing a launch signal in association with the visual cue wherein a computer having an input device responsive to the launch signal is enabled thereby to access the location on the network upon the appearance of the visual cue.

2. The method of Claim 1, further comprising the step of:
attracting the consumer's attention to the computer for interacting with the location on the network in association with the access thereto.

3. The method of Claim 1, wherein the step of providing a visual cue precedes the step of releasing the launch signal.

4. The method of Claim 1, wherein the step of releasing the launch signal precedes the step of providing a visual cue.

5. The method of Claim 1, wherein the steps of providing the visual cue and releasing the launch signal occur substantially simultaneously.

6. The method of Claim 5 wherein the steps of providing the visual cue and releasing the launch signal occur substantially within a predetermined interval of time.

7. The method of Claim 1, comprising the step of:
animating the visual cue during its appearance wherein the animation is
accompanied by the launch signal.

8. The method of Claim 7, comprising the steps of:
detaching one or more moving segments from a stationary portion of the
visual cue; and

5 traversing a path with each detached segment about the stationary
portion of the visual cue to a predetermined position adjacent thereto.

9. The method of Claim 8, wherein the stationary portion of the visual cue
forms an alphanumeric character and the moving segment resembles a punctuation
mark.

10. The method of Claim 8, wherein the stationary portion of the visual cue
forms an iconic figure and the moving segment resembles an element of said iconic
figure.

11. The method of Claim 1, wherein the step of releasing a launch signal
comprises the step of:
providing a sound signal having a recognizable characteristic that is
identifiable each time it occurs.

12. The method of Claim 11, wherein the step of providing a sound signal
comprises the step of releasing a launch signal that is not audible to a human.

13. The method of Claim 12, wherein the frequency of the sound signal is
outside the range of human hearing.

14. The method of Claim 12, wherein the intensity of the sound signal is below the threshold of human hearing.

15. The method of Claim 1, wherein the step of releasing a launch signal comprises the step of:

providing a light signal having a recognizable characteristic that is identifiable each time it occurs.

16. The method of Claim 1, wherein the visual indicia includes a logo.

17. The method of Claim 1, wherein the presentation witnessed by the consumer includes a program having audio and video content.

18. The method of Claim 1, wherein the presentation witnessed by the consumer includes a broadcast communication having audio and video content.

19. The method of Claim 1, wherein the presentation witnessed by the consumer includes a live presentation.

20. The method of Claim 1, wherein the presentation witnessed by the consumer includes a recorded presentation.

21. A method for interfacing a user to the result of a control action while the user is viewing a first viewing surface, comprising the steps of:

providing the user a visual cue proximate the first viewing surface;

providing a control signal in conjunction with the visual cue, the control signal causing a control action to be taken on a user device that will cause the user device to undergo a control action to provide the result of the control action; and

wherein the visual cue is operable to train the user to anticipate the result of the control action after viewing thereof.

22. The method of Claim 24, wherein the step of providing to the user a visual cue proximate to the first viewing surface comprises the step of providing to the user a visual cue on the first viewing surface at a predetermined location thereon.

23. The method of Claim 22, wherein the first viewing surface is operable to provide to the user a broadcast video program.

24. The method of Claim 23 and further comprising, wherein the step of providing the user a visual cue comprises providing a distinct visual cue such that the visual cue can be perceptibly discriminated from the broadcast program.

25. The method of Claim 23, wherein the broadcast program includes audio in association with the broadcast program.

26. The method of Claim 21, wherein the step of providing a control signal in conjunction with the visual cue comprises providing an audio control signal.

27. The method of Claim 21, wherein the user device is a computer having a display associated therewith as a second viewing surface and the result of the control action is to provide information on the display and wherein the control signal is operable to cause the display to provide on the associated display information that is

5 associated with the presentation of the visual cue to the step of providing the visual cue to the user.

28. The method of Claim 27, wherein the step of causing the computer to display information comprises steps of:

connecting the computer through a network to a remote site on the network in response to receiving the control signal; and

5 after connecting to the remote site, returning from the remote site to the computer information associated with the control signal.

29. The method of Claim 28, wherein the visual cue is operable to train the user to view the displayed information after the step of providing to the user a visual cue.

30. The method of Claim 21, wherein the step of providing a control signal occurs before the step of providing the user a visual cue.




31. The method of Claim 21, wherein the step of providing the user a visual cue and the step of providing the control signal occur substantially simultaneously.

32. The method of Claim 21, wherein the step of providing to the user a visual cue occurs prior to the step of providing the control signal.

METHOD FOR UTILIZING VISUAL CUE IN CONJUNCTION WITH WEB ACCESS

ABSTRACT OF THE DISCLOSURE

The present invention disclosed and claimed herein comprises a visual indicia or cue for facilitating computer based access of a network by a consumer witnessing a presentation. A visual indicia or cue is provided during the presentation indicative of a relationship between the visual indicia or cue in the presence of a location on a network. This allows this location on the network to be accessed by a computer having an appropriate input device for responding to a launch signal associated with the visual indicia or cue wherein such response of the input device will connect the computer to the location.



PATH A: SOURCE TO ARS



FIG. 4a

PATH B: ARS TO SOURCE



FIG. 4b

PATH C: SOURCE TO ADVERTISER



FIG. 4c

PATH D: ADVERTISER TO SOURCE




FIG. 4d

PATH E: ARS TO ADVERTISER (OPTIONAL)




FIG. 4e




FIG. 6




FIG. 5




FIG. 7

DISPLAY




FIG. 8








FIG. 9






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18






FIG. 16a

FIG. 19



2102		2104		2106	2108	
PRODUCT		WAND		USER	E-COMMERCE	
BC	ROUTE	ID	DISTR	PROFILE	BC	INFO

2100

FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25a




FIG. 25b




FIG. 26




FIG. 26a




FIG. 27




FIG. 28A

FIG. 28B

FIG. 28C




FIG. 29A

FIG. 29B

FIG. 29C




FIG. 30

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

We believe that we are the original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention, design or discovery entitled:

METHOD FOR UTILIZING VISUAL CUE IN CONJUNCTION WITH WEB ACCESS
the specification of which is attached hereto;

We have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above; and

We acknowledge our duty to disclose to the Patent and Trademark Office all information known to us which is material to patentability as defined in 37 C.F.R. § 1.56 (a).

We hereby claim foreign priority benefits under 35 U.S.C. § 119(a) of any foreign application(s) for patent or inventor's certificate listed below and have also identified any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

NONE

We hereby claim provisional priority benefits under 35 U.S.C. § 119(e) of any provisional application(s) for patent or inventor's certificate listed below and have also identified any provisional application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

NONE

We hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C § 112, I acknowledge the duty to disclose material information as defined 37 C.F.R. § 156 (a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

NONE

We hereby appoint:

Gregory M. Howison, Reg. No. 30,646
 Roger N. Chauza, Reg. No. 29,753
 Mark W. Handley, Reg. No. 36,821
 John J. Arnott, Reg. No. 39,095
 Stephen S. Mosher, Reg. No. 33,974
 William Gustavson, Reg. No. 29,160

of the firm HOWISON, CHAUZA, HANDLEY & ARNOTT, L.L.P., my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, and to file and prosecute any international patent applications based thereon in any foreign country or before any international authorities under the Patent Cooperation Treaty.

Send Correspondence To:

HOWISON, CHAUZA, HANDLEY & ARNOTT, L.L.P.
 P.O. Box 741715
 Dallas, Texas 75374-1715

Direct Telephone Calls To:

Gregory M. Howison
 at (972) 479-0462
 Atty. Docket No. PHL-25,509

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of the First Joint Inventor: **Jeffrey Jovan Philyaw**

Inventor's Signature: _____

Date: _____

Residence (City, State): **Dallas, Texas 75225**

Citizenship: **US**

Post Office Address: **5968 West Northwest Highway #1813, Dallas, Texas 75225**

Full name of the Second Joint Inventor: **David Kent Mathews**

Inventor's Signature: _____

Date: _____

Residence (City, State): **Carrollton, Texas 75007**

Citizenship: **US**

Post Office Address: **3438 Livingston Lane, Carrollton, Texas 75007**